214.3237

PLUG
32A 3P+N+E 6h 346-415V 60Hz 50Hz
Screw terminals



* Product image may be indicative

EN IEC 60309-1 (2022)
EN IEC 60309-2 (2022)
Low voltage direct. 2014/35/EU

GENERAL CHARACTERISTICS

Commercial Series	XENIA Series
Synthetical description	PLUG
Description	

The plug from the XENIA Series is engineered for a rated voltage of 346-415V and a current of 32A. Featuring 3P+N+E poles and a 6h hour position, it operates efficiently at both 50Hz and 60Hz frequencies. With a protection degree of IP44/IP54, it offers reliable performance in various environments. The plug is equipped with screw terminals and is compatible with straight type outlets. This robust design ensures dependable functionality for professional applications.

Mounting version	PORTABLE

TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP44/IP54
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND
Halogen free	HALOGEN FREE

DOWNLOAD

Technical drawing [PDF]
Technical drawing [STP]
Technical drawing [DWG]